

Motorlüfterrad einflutrig

Motorized impeller single inlet

RH45M-VDK.4F.1R

Art.Nr. mit Kabelbox
Art.no. with supply cable adapter

113 004




Leistungsdaten Performance data

3~ 400V ±10% Δ/Y
50Hz IP54

Anschlussschaltbild 108XA
Connection diagram

P ₁	0,69/0,35	kW
I	1,3/0,68	A
n	1210/830	min ⁻¹
I _A	3,4/1,95	A
ΔI	0	%
t _R	40	°C
m	9,0	kg



Kennliniendaten Characteristic data



	U	I	P ₁	n	L _{WA}
	V	A	W	min ⁻¹	dB
①		1,05	500	1330	
②	400Δ	1,3	690	1210	74
③		1,15	580	1290	83
④		0,58	310	990	
⑤	400Y	0,68	350	830	65
⑥		0,64	330	930	75

$$p_{d2} = 9,4 \cdot 10^{-7} \cdot q_v^2$$

SONDERAUSFUEHRUNG AUF ANFRAGE
MIT KABEL SEITLICH ODER MIT KLEMMENKASTEN /
SPEZIAL DESIGN ON REQUEST
WITH CABLE SIDE OR WITH TERMINAL BOX



L-KL-1784/3-D02